

Non-pressurized Solar Water Heater

ITEM	Vacuum Tubes		Collector Area/m ²	Capacity Tank/ Lts	Loading Qty (sets)			Quantity
	Qty / Pieces	Size/mm			20GP	40GP	40HQ	
BSI-NP16	16	Ø/47 X 1500	1.57	100	62	129	152	
BSI-NP18	18	Ø/47 X 1500	1.76	110	57	117	139	
BSI-NP20	20	Ø/47 X 1500	1.96	120	53	110	131	
BSI-NP24	24	Ø/47 X 1500	2.35	140	43	89	105	
BSI-NP30	30	Ø/47 X 1500	2.94	180	36	75	89	
BSI-NP36	36	Ø/47 X 1500	3.53	200	30	63	74	

Inner Tank: Food-grade stainless steel SUS304-2B 0.4mm.

Outer Tank: Stainless steel SUS202 0.4mm.

Bracket: Stainless steel plate 1.2mm, suitable for slop and flat roof. Angle of bracket : 25°-50°.

Heat Insulation: High density polyurethane integrated foam-forming layer.

Vacuum Tube: Borosilicate glass vacuum tube, ALN(H)/AL-ALN(L)/ALN coating.

Hot water : 45-95°C.

Accessories: Stainless bolt & nut, silicon rubber seal, dustproof rubber ring, plastic pipe holder, air-vent cap.

Warranty: 3 years for whole system and 15 years for vacuum tube.

Certificates: CE, ISO 9001.

